



EAST BRUNSWICK FIRE DISTRICT #1

BUREAU OF FIRE SAFETY
680 OLD BRIDGE TURNPIKE
EAST BRUNSWICK, N.J. 08816
TEL: (732) 651-8806
FAX: (732) 257-0960

APPLICATION FOR PERMIT

The Uniform Fire Code states:

"Permits shall be required, and obtained from the local enforcing agency for the activities specified in this section, except where they are an integral part of a process or activity by reason of which a use is required to be registered and regulated as a life hazard use. Permits shall at all times be kept in the premises designated therein and shall at all times be subject to inspection by the fire marshal." [N.J.A.C. 5:70-2.7(a)]

Date of application: _____

Location where activity will occur _____

Date _____ Time _____

Applicant Name _____ Address _____

Organization Name _____

Phone/Fax Number _____ Emerg.# _____

Block/Lot _____ Registration#: _____

The above named applicant hereby requests permission to conduct the following activity at the above indicated location:

And for the keeping, storage, occupancy, sale, handling or manufacture of the following:

(State quantities for each category to be stored, or used and the method stored or used:)

I hereby acknowledge that I have read this application, that the information given is correct, and that I am the owner, or duly authorized to act in the owner's behalf and as such hereby agree to comply with the applicable requirements of the fire code as well as any specific conditions imposed by the fire marshal.

Applicant Signature

Fire Marshal Signature

Fee Amount

Permit Type



BUREAU OF FIRE SAFETY

EAST BRUNSWICK FIRE DISTRICTS #1 & #3
680 OLD BRIDGE TURNPIKE
EAST BRUNSWICK, N.J. 08816
TEL: (732) 651-8806
FAX: (732) 257-0960

Please fill out the attached application for the required permits under the NJ Uniform Fire Code N.J.A.C.5:70-2.7 and the East Brunswick Fire Safety Code Chapter 102 in full and return it along with the appropriate permit fees payable to:

East Brunswick Fire District #1
680 Old Bridge Turnpike
East Brunswick, NJ 08816

Permit Fees

Food Vendors with propane/LPG gas:

3-49 gallons/12-200 pounds	54.00
50-199 gallons / 201 – 840 pounds	100.00
200-999 gallons / 841 – 4,235 pounds	200.00
1,000 – 2,000 gallons / 4,236 – 8,480 pounds	300.00

Food Vendors without propane	25.00
Open Flame or flame producing device (charcoal Grills)	54.00

Outside Vendors selling/displaying merchandise	25.00
Vendors in the large tents	10.00

PERMITS MAY BE REVOKED & PENALTIES ISSUED FOR FAILURE TO COMPLY

SMOKE DETECTORS SAVE LIVES!

GENERAL SAFETY

SECTION 102

102.1 GENERAL. The following provisions are general precautions to be applied to the use of all properties.

- 102.1.1. Any dangerous or hazardous conditions that are outlined in items 1 through 10 below shall be removed or remedied in accordance with the provisions of N.J.A.C. 5:70-2.10:
1. Dangerous conditions that are liable to cause or contribute to the spread of fire in or on said premises, building or structure or endanger the occupants thereof;
 2. Conditions that would interfere with the efficiency and use of any fire protection equipment;
 3. Obstruction to or on fire escapes, stairs passageways, doors or windows, liable to interfere with the egress of occupants or the operation of the fire department in case of fire;
 4. Accumulations of dust or waste material in air conditioning or ventilating systems or grease in kitchen or other exhaust ducts;
 5. Accumulations of grease on kitchen cooking equipment, or oil, grease or direct upon, under or around any mechanical equipment;
 6. Accumulations of rubbish, waste, paper, boxes, shavings or other combustible materials or excessive storage of any combustible material;
 7. Hazardous conditions arising from defective or improperly used or installed electrical wiring, equipment or appliances;
 8. Hazardous conditions arising from defective or improperly installed equipment for handling or use of combustible, explosive or otherwise hazardous materials;
 9. Dangerous or unlawful amounts of combustible, explosive or otherwise hazardous materials; or
 10. All equipment, materials, processes or operations that are in violation of the provisions and intent of this code.

FIRE PROTECTION SYSTEMS

FOOD VENDORS COOKING WITH PROPANE OR OPEN FLAME

EVERY COOKING VENDOR "MUST" HAVE A CLASS "K" EXTINGUISHER

901.5.1. **Inspection, testing and maintenance.** Any installed fire detection, alarm and extinguishing systems, smoke control, smoke and heat vents whether in a permanent structure or a mobile enclosed unit shall be maintained in an operative condition at all times, and shall be replaced or repaired where defective.

Alternative Automatic Fire Extinguishing Systems

904.2.1. **Commercial hood and duct systems.** Each required commercial kitchen exhaust hood and duct system required by Section 609 to have a Type I hood including mobile enclosed cooking operations shall be maintained in accordance with this code.

904.11.5 **Portable fire extinguishers for commercial cooking equipment.** Portable fire extinguishers shall be provided within a 30-foot (9144 mm) travel distance of commercial-type cooking equipment. Cooking equipment involving vegetable or animal oils and fats shall be protected by a Class "K" rated portable extinguisher.

904.11.5.1 **Portable fire extinguishers for solid fuel cooking appliances.** All solid fuel cooking appliances, whether or not under a hood, with fireboxes 5 cubic feet (0.14 m³) or less in volume shall have a minimum 2.5 gallon (9L) or two 1.5 gallon (6L) Class "K" wet-chemical portable fire extinguishers located in accordance with Section 904.11.5

- 904.11.5.2 Class "K" portable fire extinguishers for deep fat fryers. When hazard areas include deep fat fryers, listed Class "K" portable fire extinguishers shall be provided as follows:
1. For up to four fryers having a maximum cooking medium capacity of 80 pounds (36.3 kg) each: One Class "K" portable fire extinguisher of a minimum 1.5 gallon (6L) capacity.
 2. For every additional group of four fryers having a maximum cooking medium capacity of 80 pounds (36.3 kg) each: One additional Class "K" portable fire extinguisher of a minimum 1.5 gallon (6L) capacity shall be provided.
 3. For individual fryers exceeding 6 square feet (0.55m²) in surface area: Class "K" portable fire extinguishers shall be installed in accordance with the extinguishers shall be installed in accordance with the extinguisher manufacturer's recommendations.
- 904.11.6 **Operations and maintenance.** Commercial cooking systems, including mobile enclosed cooking operations, shall be operated and maintained in accordance with this section.
- 904.11.6.4 **Extinguishing system service.** Automatic fire-extinguishing systems shall be serviced at least every 6 months and after activation of the system. Inspection shall be by qualified individuals, and a certificate of inspection shall be forwarded to the fire code official upon completion.

TENTS, CANOPIES AND OTHER MEMBRANE STRUCTURES

- 2403.7 **Inspections.** The entire tent, air-supported, air-inflated or tensioned membrane structure system shall be inspected at regular intervals but not less than two times per permit use period, by the permittee, owner or agent to determine that the installation is maintained in accordance with this chapter.
- 2403.7.1 **Inspection Report.** When required by the fire code official, an inspection report shall be provided and shall consist of maintenance, anchors and fabric inspections.
- 2403.8.2 **Location.** Tents, canopies or membrane structures shall not be located within 5 feet (1524 mm) of lot lines, buildings, other tents, canopies or membrane structures, parked vehicles or internal combustion engines.
- 2404.6 **Smoking.** Smoking shall not be permitted in tents, canopies or membrane structures. Approved "No Smoking" signs shall be conspicuously posted in accordance with Section 310.
- 2404.7 **Open or exposed flame.** Open flame or other devices emitting flame, fire or heat or any flammable or combustible liquids, gas, charcoal or other cooking device or any other unapproved devices shall not be permitted inside or located within 20 feet (6096 mm) of the tent, canopy or membrane structures while open to the public unless approved by the fire code official.
- 2404.15.1 **Installations.** Heating or cooking equipment, tanks, piping, hoses, fittings, valves, tubing and other related components shall be installed as specified in the mechanical sub-code and the fuel gas sub-code of the Uniform Construction Code and shall be approved by the fire code official.
- 2404.15.3 **Location.** Suitable barricades shall be provided to maintain a distance of 5 feet (1524 mm) between the heat producing appliances and the public.
- 2404.15.5 **Cooking tents.** Tents where cooking is performed shall be separated from other tents, canopies or membrane structures by a minimum of 5 feet (1524 mm).
- EXCEPTIONS:**
- Cooking tents shall be separated from other tents, canopies or membrane structures with an occupant load of 50 or greater by a minimum of 20 feet (6096 mm).
- 2404.16.1 **LP-gas General.** LP-gas equipment such as tanks, piping, hoses, fittings, valves, tubing and other related components shall be approved and in accordance with Chapter 38 and with the fuel gas sub-code of the Uniform Construction Code.
- 2404.16.2 **Location of Containers.** LP-gas containers shall be located outside or on the exterior perimeter of a canopy. Safety release valves shall be pointed away from the tent, canopy or membrane structure.
- 2404.16.2.1 **Containers.** LP-gas containers shall be located a minimum of 5 feet (1524 mm) from any heat producing appliance.
- 2404.16.3 **Protection and security.** Portable LP-gas containers, piping, valves and fittings which are located outside and are being used to fuel equipment inside a tent, canopy or membrane structure shall be adequately protected to prevent tampering, damage by vehicles or other hazards and shall be located in an approved location. Portable LP-gas containers shall be securely fastened in place to prevent unauthorized movement.

PROPANE STORAGE AND SAFETY

- 3807.2 **Smoking and other sources ignition.** "NO SMOKING" signs complying with Section 310 shall be posted when required by the fire code official. Smoking within 25 feet (7620 mm) of a point of transfer, while filling operations are in progress at containers or vehicles, shall be prohibited.
- 3807.5 **Container markings.** Containers of 100 pounds (45 kg) or more water capacity shall be legibly marked with a warning following by the name of the gas contained. The warning label shall read "Flammable Gas" followed by the name of the gas, such as "propane" or "Butane".
- 3807.6 **Storage area signs.** Storage areas having containers exceeding 100 pounds (45 kg) product water capacity shall be posted with adequate "NO SMOKING" and "FLAMMABLE GAS" signs marked legibly. The "FLAMMABLE GAS" and the name of the gas to indicate the contents such as "FLAMMABLE GAS-PROPANE" or "FLAMMABLE GAS-BUTANE".
- 3809.13 **Protection of containers.** Containers shall be stored with a suitable enclosure or otherwise protected against tampering. Vehicular protection shall be provided as required by the fire code official.
- 3809.14 **Alternative location and protection of storage.** Containers located outside of building shall not be located within 20 feet (6096 mm) of any exit access doors, exits, stairways or in areas normally used, or intended to be used, as a means of egress.